

MultiSync® 20WGX²Pro





Entertainment displays with fastest response time and glossy surface – for vibrant image reproduction.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- Safety of investment with analog/digital interface and integrated USB hub
- Rapid Response technology 6 ms (grey-to-grey)
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment) and S-IPS TFT display
- OptiClear DVM for outstanding image clarity and vibrant colours

MultiSync® 20WGX²Pro

| TECHNICAL SPECIFICATIONS | |
|---|---|
| Panel Technology | S-IPS TFT |
| Screen Size [inch/cm] | 20.1 / 51.1 |
| Pixel Pitch [mm] | 0.258 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 10:1) |
| Contrast Ratio (typ.) | 700:1; (1600:1 with Advanced DV Mode) |
| Brightness (typ.) [cd/m²] | 470 |
| Response Time (typ.) [ms] | 6 (grey-to-grey), 12 (tr - tf) |
| Colours [Mio.] | 16.77 |
| Horizontal Frequency [kHz] | 31.5 - 81.1 |
| Vertical Frequency [Hz] | 56 - 75 |
| Optimum Resolution | 1680 x 1050 at 60 Hz |
| Supported Resolutions | 1440 x 900; 1400 x 1050; 1360 x 768; 1280 x 1024; 1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480 |
| Connectors | Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin |
| Plug & Play | VESA DDC/CI; DDC2B/2Bi; EDID Standard |
| Adjust Functions | Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Intelligent Power Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Manager (OSM) lock-out; sRGB |
| Safety and Ergonomics | CE; TCO 06; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS |
| Power Consumption on Mode [W] | 69 (typ.) |
| Power Consumption Power-Saving Mode [W] | <2 |
| Power Supply | 100-120 V/220-240 V; 1.2 A/0.6 A; internal power supply |
| Ambient Temperature (operating) [°C] | +5 to +35 |
| Ambient Humidity (operating) [%] | 30 to 80 |
| VESA Mounting [mm] | 100 x 100 |
| Screen Tilt / Swivel [°] | -5 to +30 / -170 to +170 |
| Dimensions (W x H x D) [mm] | 471.4 x 391.5 x 203 |
| Bezel Width [mm] | 18.1 |
| Weight [kg] | 6.3 |
| Cable Management | yes |
| Kensington Lock | yes |
| OptiClear DVM | yes |
| Benefits | 16:10 wide format; NaViSet® and NaViSet® Administrator compatible; OptiClear DVM; Power-Off Timer; Rapid Response Technology; sRGB Support; USB ver. 2.0 (4 down / 1 up) |
| Audio Functions | Option: MultiSync® Soundbar 20W |
| Colour Versions | Silver Front Bezel, Black Back Cabinet |
| Shipping Content | Monitor; Power Cable; Signal Cable VGA - VGA, DVI-D - DVI-D; USB Cable; CD-ROM; Sales Office List; User Manual |
| Warranty | 3 years warranty incl. backlight |
| | · |





























