GXA-750/GXA-1600

PROFESSIONAL STEREO AMPLIFERS

Both the GXA-750 & 1600 are powerful amplifiers that will ensure solid sound stability with a constant performance.

These amplifiers will operate at 8, 4 & 2 ohms with mono or bridge modes, enabling a user to utilize each in a variety of ways with different sound systems. The monitoring systems use various LEDs for proper indication of distortion and different operating modes.

We have also included balanced inputs & outputs for improved connectivity, resulting in a very useful solution for most DJs.

FEATURES:

- State of the art technology provides exceptional reliability when working with difficult speakers
- · Stable down to 2 ohm impedence
- · Excellent handling of low frequencies as well as clear mids and flawless highs
- High output power to drive professional loudspeakers without distortion
- Oversized toroidal transformer, filter and heatsinks for better low end, transparency and stability
- Comprehensive protection circuitry (short, overheat, DC, subsonic & RF filters, turn-on delay) with high current speaker protection relays
- Three modes of operation stereo, parallel mono and mono bridge with mode status indication LED on front panel
- Flexible input configuration with active balanced inputs; additional input connectors to chain amps
- . True clip LED for better control
- · Front-to-Rear airflow with 2 speed dual fan control
- Efficient dual aluminum extrusion heatsink design for thermal stability & reliability
- · Turn-on in-rush current limiting circuitry
- · Compact 2U well balanced enclosure
- · Steel reinforced chassis construction for durability and longevity
- · Backed by an extended five year warranty



6XA-750



6XA-1600



REAR PANEL

	Mono bridge		Single channel			Both channels				
	$ 4\Omega$	8Ω	2Ω	4Ω	8Ω	2Ω	4Ω	8Ω	Watts	
GXA-750	750	550	470	325	190	360	275	175	DMS	
GXA-1600	1600	1000	950	600	340	800	500	300	KIVIO	



MONO & BRIDGE MODE LEDS



ROTARY VOLUME CONTROLS FOR BOTH CHANNELS



Gemini Worldwide Headquarters 120 Clover Place, Edison, NJ 08837 • USA Tel: (732) 738-9003 • Fax: (732) 738-9006

E-mail: sales-usa@geminidj.com Web: www.geminidj.com © Gemini Sound Products Corp. 2004 All Rights Reserved.



MODERN NEUTRIK OUTPUT CONNECTORS



BALANCED XLR & 1/4" INPUTS



PROTECTION, CLIP & SIGNAL LEDS